

# HEATZONE®

# H750 Flameless Heater

This system is so simple, easy to operate and efficient – it **will revolutionize** the “flameless heat market!”

## FUNCTION AND DESIGN FEATURES:

- 7,300 CFM thru one 16" duct
- >20" Static Pressures
- Maximum heat output—250° F (121° C)
- Two temperature settings (high – low)
- Gross Btu per hour 906,500
- Net Btu per hour 725,000
- Cummins Power Generation package (119 HP, 80 KW)
- Positive air shut-off
- Trailer measures L 183.875" x W 96.8125" x H 78.375"
- 110% total containment
- Maximum fuel consumption 7 GPH (26.5 LPH)
- Fuel capacity 240 gallons (908.5 Liters)
- Optional 8 KW light tower package

## SPECIFICATIONS

Fuel Capacity	240 Gallons (908.5 Liters)
Engine	Cummins diesel
Fuel Burn	7 GPH (26.5 LPH)
L x W x H	183.875" x 96.8125" x 78.375"
Weight	8,200# with fuel
Outlet Ducts	1 – 16" input, 1 – 16" output
Air handler	Two – stage blower
Heat Settings	High, Low
Max. Heat output	250° F (121° C)
CFM	7,300 CFM
Static Pressure	>20"
Net Btu	761,460
Liquid containment	110%
Positive air shut-off	YES
Optional Light tower	8 KW LED
Hydraulic Fluid	None



The H750 is the most reliable flameless heater on the market with the highest output of heat and CFM. No hydraulic fluid, so no need to flush and change.

*Now taking orders for delivery.*



HeatZone®  
A Division of Thawzall, LLC

[www.thawzall.com](http://www.thawzall.com)

106 Donovan Drive • Alexandria, MN 56308  
Ph: 320-759-1588 • Fax: 320-759-1583  
Toll Free 888-757-3545