

THAWZALL

Tamarack Industries

TCH 250 MOBILE GLYCOL HEATING SYSTEMS



FEATURES


- 5-600FT HOSES
- THAW UP TO 6,000 FT²
- CURE UP TO 12,000 FT²
- TEMPORARY HEAT UP TO 12,000 FT²
- OVER 3 DAYS RUN TIME
- RETURN TEMPERATURE INDICATORS ON ALL 5 ZONES
- BI-DIRECTIONAL POWERED REEL WITH FREEWHEEL FEATURE
- SIMPLE TO OPERATE WITH 1 SWITCH
- HEATZONE FLUID DISTRIBUTION

WWW.THAWZALL.COM



SIMPLE & EFFICIENT

- 1 SWITCH START UP with Digital Monitoring
- HEAT ZONE FLUID DISTRIBUTION TECHNOLOGY
- THREE WAY MIXING VALVE PROVIDES PRECISE TEMPERATURE OUTLET CONTROL. THE BEST FOR CONCRETE CURING.



TCH 250 SPECIFICATIONS

• Hose	5 - 600 ft Field Hoses (5/8" Hose)	• Interior Lights	Standard for ease of night operation
• Hose	Unspool with one person	• Heater Capacity Diesel	280,000 BTU/H Heating Fuel Input
• Supply Manifold	5 - 3/4" quick connect & 1 - 1" quick connect	• Electrical Requirements	1 - 120V AC 20A Circuits
• Return Manifold	5 - 3/4" quick connect & 1 - 1" quick connect	• Generator (Optional)	1 - 7,000W
• Ground Thawing Capacity	up to 6,000 ft ²	• Hitch	2 5/16" Ball (Pintle also available)
• Concrete Curing Capacity	up to 12,000 ft ²	• Dimensions	170"x84"x93"
• Temporary Heating Capacity	12,000 ft ² (Varies with R-Value)	• Weight (Fuel Full)	5900 lbs
• Field Pump	1/2 Hp closed Loop Centrifugal		
• Fuel Tank	150 US GAL DOUBLE WALL TANK		
• Run Time	Up to 100 Hours (with Genset)		
• Fuel Consumption	TCH 250 = 2.06 GPH, Genset = .55 GPH		